

LED Track Light D Series Specifications





- For 2 wires, 3 wires and 4 wires track or surface mounting.
- External driver box design, 10W-50W
- CREE COB, 80Ra,
- Rotation angle 350°, Swivel angle 350°
- Colors: White/Black
- 5 years warranty
- Aluminum 6063 Housing
- 0-10V/DALI Dimming available
- Lifud driver, 220-240V AC 50/60 Hz, PF>0.95 (Tridonic, Osram and Philips optional)



Model No.:	Power	LED Current	Light efficiency (type)	Color rendering index	Color Temperature	Beam angle	Working temperature
BST-TL-10W-D	10W	250mA	>85lm/W	>80Ra	2700-5000K	15°, 24°36°, 60°	-30℃~+45℃
BST-TL-20W-D	20W	500mA	>85lm/W				
BST-TL-30W-D	30W	700mA	>85lm/W				
BST-TL-40W-D	40W	950mA	>90lm/W				
BST-TL-50W-D	50W	1200mA	>90lm/W				

CREE COB only can reach 5000K, if 6000K is requested, please choose CITIZEN COB.

The photometric values are standard values and refer to the entire luminaire. In the case of CRI ≥ 90, the efficiency is approx. 10-15 % lower.



Dimension

10-30W



40-50W



Packing(10PCS/CTN)

10W Carton: 64.3*24.3*37CM N.W:0.85KG G.W:11.5KG/CTN
 20W Carton: 64.3*24.3*37CM N.W:0.85KG G.W:11.5KG/CTN
 30W Carton: 64.3*24.3*37CM N.W:0.85KG G.W:11.5KG/CTN
 40W Carton: 64.3*24.3*37CM N.W:1.05KG G.W:14KG/CTN
 50W Carton: 64.3*24.3*37CM N.W:1.05KG G.W:14KG/CTN

